

## The F400 Fuel Oil Stove



A new category of freestanding room heaters powered by fuel oil is appearing in North America. They offer convenient, powerful zone heating in a stylish cast iron body at about the same cost per hour as natural gas.



- Six settings from low to high to control heat output (A).
- No electricity is required for operation.
- Minimum heat output of 9,100 Btu/hr. and maximum heat output of 35,400 Btu/hr. for the F400; Minimum heat output of 11,800 Btu/hr. and maximum heat output of 48,900 Btu/hr. for the F750.
- Fuel consumption on low is 0.095 gal/hr. and on high is 0.38 gal/hr. for the F400; Fuel consumption on low is 0.127 gal/hr. and on high is 0.476 gal/hr. for the F750.
- A catalyst creates a mixture of air and fuel to produce a clean and efficient burn (B).
- Requires a 5" L-vent or a 6" Class A vent.
- An optional wall thermostat controls heat output.
- Up to 80% efficient.
- Available in standard matte black or optional porcelain puritan black, french blue, bavarian green or jersey creme.
- Safety listed by Warnock Hersey for use in the U.S. and Canada.

## The F750 Fuel Oil Stove

Homeowners without natural gas now have an economical, convenient, reliable room heating option to the traditional wood stove. All you need is an oil tank and chimney with your Dove oil stove and you'll be ready for winter!



### Why Choose A Fuel Oil Stove?

- No electricity is required, allowing for operation even during power outages.
- Uses easily available furnace fuel which is more economical than propane (approximately a 50% cost savings).
- Highly efficient (up to 80%).
- Convenience — many homes already have oil supplied to them.
- Environmentally friendly.
- Oil is safer in the home than gas or propane.
- Large Btu output warms the room.
- Realistic wood-looking log-set that glows red.

### Clearances to Single Wall Connector

	F400	F750
Sidewall to unit	13"	9"
Backwall to unit	18"	18"
Corner to unit	13"	8"
Backwall to connector	9"	9"
Maximum alcove depth	36"	36"

### Clearances to Vented Double Wall Connector

	F400	F750
Sidewall to unit	7"	9"
Backwall to unit	15"	15"
Corner to unit	7"	5"
Backwall to connector	6"	6"
Maximum alcove depth	36"	36"

### Dimensions

	F400	F750
Height	29 1/2"	29 1/2"
Width	22 3/4"	28"
Depth	14 3/4"	19"

Stop By And Ask About One Today At:

# DOVRE.

Exclusive distributor

DRAGON FIRE DISTRIBUTION INC.

PH: 1-877-321-8111

Website: [www.dovreoilstove.com](http://www.dovreoilstove.com)

# Finally an Affordable Alternative!

F400 and F750 Fuel Oil Stoves



# DOVRE.

F400 and F750  
Fuel Oil Stoves